

**描述 / Descriptions**

TO-92 塑封封装 NPN 半导体三极管。Silicon NPN transistor in a TO-92 Plastic Package.

**特征 / Features**


耐压高，快速转换。

High Voltage Capability High Speed Switching.

**用途 / Applications**

主要用于节能灯、日光灯电子镇流器及其它开关、振荡电路。

High frequency electronic lighting ballast applications, converters, inverters, switching regulators, etc.

**内部等效电路 / Equivalent Circuit****引脚排列 / Pinning**

PIN1 : Emitter

PIN 2 : Collector

PIN 3 : Base

**放大及印章代码 / hFE Classifications & Marking**

见印章说明。See Marking Instructions.









**极限参数 / Absolute Maximum Ratings(Ta=25°C)**

| 参数<br>Parameter                | 符号<br>Symbol           | 数值<br>Rating | 单位<br>Unit  |
|--------------------------------|------------------------|--------------|-------------|
| Collector to Base Voltage      | $V_{CBO}$              | 600          | V           |
| Collector to Emitter Voltage   | $V_{CEO}$              | 400          | V           |
| Emitter to Base Voltage        | $V_{EBO}$              | 9.0          | V           |
| Collector Current - Continuous | $I_C$                  | 0.45         | A           |
| Collector Power Dissipation    | $P_C(T_a=25^{\circ}C)$ | 1.0          | W           |
| Junction Temperature           | $T_j$                  | 150          | $^{\circ}C$ |
| Storage Temperature Range      | $T_{stg}$              | -55~150      | $^{\circ}C$ |

**电性能参数 / Electrical Characteristics(Ta=25°C)**

| 参数<br>Parameter                         | 符号<br>Symbol  | 测试条件<br>Test Conditions            | 最小值<br>Min | 典型值<br>Typ | 最大值<br>Max | 单位<br>Unit |
|-----------------------------------------|---------------|------------------------------------|------------|------------|------------|------------|
| Collector to Base Breakdown Voltage     | $V_{CBO}$     | $I_C=1mA$ $I_E=0$                  | 600        |            |            | V          |
| Collector Cut-Off Current               | $V_{CEO}$     | $I_C=10mA$ $I_B=0$                 | 400        |            |            | V          |
| Emitter Base Cut-Off Current            | $V_{EBO}$     | $I_E=1mA$ $I_C=0$                  | 9.0        |            |            | V          |
| Collector Cut-Off Current               | $I_{CBO}$     | $V_{CB}=600V$ $I_E=0$              |            |            | 0.1        | mA         |
| Collector cut-off current               | $I_{CEO}$     | $V_{CE}=400V$ $I_B=0$              |            |            | 0.1        | mA         |
| Emitter Base Cut-Off Current            | $I_{EBO}$     | $V_{EB}=9.0V$ $I_C=0$              |            |            | 0.1        | mA         |
| DC Current Gain                         | $h_{FE}$      | $V_{CE}=5.0V$ $I_C=100mA$          | 10         |            | 40         |            |
| Collector to Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_C=100mA$ $I_B=20mA$             |            |            | 0.5        | V          |
| Base to Emitter Saturation Voltage      | $V_{BE(sat)}$ | $I_C=100mA$ $I_B=20mA$             |            |            | 1.2        | V          |
| Transition Frequency                    | $f_T$         | $V_{CE}=10V$ $f=1.0MHz$ $I_C=50mA$ | 5.0        |            |            | MHz        |
| Fall time                               | $t_f$         | $V_{CE}=5V$ $I_C=100mA$ (UI9600)   |            |            | 0.6        | $\mu s$    |
| Storage time                            | $t_S$         |                                    |            |            | 3.0        | $\mu s$    |


## 电参数曲线图 / Electrical Characteristic Curve




外形尺寸图 / Package Dimensions

TO-92

Unit: mm



印章说明 / Marking Instructions



说明：

BR: 为公司代码

13002 : 为型号代码

E1: 规格代码

\*\*\*\* : 为生产批号代码，随生产批号变化。

Note:


BR: Company Code.

13002: Product Type.

E1: Specification Code.

\*\*\*\*: Lot No. Code,code change with Lot No.

## 波峰焊温度曲线图(无铅) / Temperature Profile for Dip Soldering(Pb-Free)



说明：

- 1、预热温度 25~150°C，时间 60~90sec;
- 2、峰值温度 260±5°C，时间持续为 5±0.5sec;
- 3、焊接制程冷却速度为 2~10°C/sec.

Note:

- 1.Preheating:25~150°C, Time:60~90sec.
- 2.Peak Temp.:260±5°C, Duration:5±0.5sec.
3. Cooling Speed: 2~10°C/sec.

## 耐焊接热试验条件 / Resistance to Soldering Heat Test Conditions

温度：270±5°C

时间：10±1 sec.

Temp:270±5°C

Time:10±1 sec

## 包装规格 / Packaging SPEC.

散件包装 / BULK

| Package Type<br>封装形式 | Units 包装数量       |                       |                        |                              |                        | Dimension 包装尺寸 (unit: mm3) |             |             |
|----------------------|------------------|-----------------------|------------------------|------------------------------|------------------------|----------------------------|-------------|-------------|
|                      | Units/Bag<br>只/袋 | Bags/Inner Box<br>袋/盒 | Units/Inner Box<br>只/盒 | Inner Boxes/Outer Box<br>盒/箱 | Units/Outer Box<br>只/箱 | Bag 袋                      | Inner Box 盒 | Outer Box 箱 |
| TO-92                | 1,000            | 10                    | 10,000                 | 5                            | 50,000                 | 135×190                    | 237×172×102 | 560×245×195 |
|                      | 1,000            | 10                    | 10,000                 | 10                           | 100,000                | 135×190                    | 237×172×102 | 560×245×375 |

编带包装 / AMMO

| Package Type<br>封装形式 | Units 包装数量         |                        |                         |                              |                        | Dimension 包装尺寸 (unit: mm3) |                                   |
|----------------------|--------------------|------------------------|-------------------------|------------------------------|------------------------|----------------------------|-----------------------------------|
|                      | Units/tape<br>只/纸带 | Tape/Inner Box<br>纸带/盒 | Rows/Inner Box<br>纸带层/盒 | Inner Boxes/Outer Box<br>盒/箱 | Units/Outer Box<br>只/盒 | Inner Box 盒                | Outer Box 箱                       |
| TO-92                | 3,000              | 1                      | 120                     | 10                           | 30,000                 | 328×230×42                 | 小箱 480×346×235,<br>大箱 547×407×268 |

## 使用说明 / Notices