




HTIP41C

NPN EPITAXIAL PLANAR TRANSISTOR

Description

The HTIP41C is designed for use in general purpose amplifier and switching applications.



Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$)

- Maximum Temperatures
Storage Temperature $-55 \sim +150^{\circ}\text{C}$
Junction Temperature $+150^{\circ}\text{C}$ Maximum
- Maximum Power Dissipation
Total Power Dissipation ($T_C=25^{\circ}\text{C}$) 65 W
Total Power Dissipation ($T_A=25^{\circ}\text{C}$) 2 W
- Maximum Voltages and Currents
 BV_{CBO} Collector to Base Voltage 100 V
 BV_{CEO} Collector to Emitter Voltage 100 V
 I_C Collector Current 6 A

Electrical Characteristics ($T_A=25^{\circ}\text{C}$)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV_{CBO}	100	-	-	V	$I_C=1\text{mA}$, $I_E=0$
BV_{CEO}	100	-	-	V	$I_C=30\text{mA}$, $I_B=0$
I_{CES}	-	-	400	μA	$V_{CE}=100\text{V}$, $I_B=0$
I_{CEO}	-	-	700	μA	$V_{CE}=60\text{V}$, $I_B=0$
I_{EBO}	-	-	1	mA	$V_{EB}=5\text{V}$, $I_C=0$
$*V_{CE(sat)}$	-	-	1.5	V	$I_C=6\text{A}$, $I_B=600\text{mA}$
$*V_{BE(on)}$	-	-	2	V	$I_C=6\text{A}$, $V_{CE}=4\text{V}$
$*h_{FE1}$	30	-	-		$I_C=0.3\text{A}$, $V_{CE}=4\text{V}$
$*h_{FE2}$	15	-	75		$I_C=3\text{A}$, $V_{CE}=4\text{V}$
f_T	3	-	-	MHZ	$V_{CE}=10\text{V}$, $I_C=500\text{mA}$, $f=1\text{MHz}$







*Pulse Test: Pulse Width $\leq 380\mu\text{s}$, Duty Cycle $\leq 2\%$

Classification Of h_{FE2}

Rank	A	B
h_{FE2}	15-50	40-75




Characteristics Curve





TO-220AB Dimension



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of HSMC.
- HSMC reserves the right to make changes to its products without notice.
- **HSMC semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- HSMC assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:


- **Head Office** (Hi-Sincerity Microelectronics Corp.): 10F., No. 61, Sec. 2, Chung-Shan N. Rd. Taipei Taiwan R.O.C.
Tel: 886-2-25212056 Fax: 886-2-25632712, 25368454
- **Factory 1:** No. 38, Kuang Fu S. Rd., Fu-Kou Hsin-Chu Industrial Park Hsin-Chu Taiwan. R.O.C
Tel: 886-3-5983621~5 Fax: 886-3-5982931



Soldering Methods for HSMC's Products

1. Storage environment: Temperature=10°C~35°C Humidity=65%±15%
2. Reflow soldering of surface-mount devices

Figure 1: Temperature profile



Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	<3°C/sec	<3°C/sec
Preheat		
- Temperature Min (T_{Smin})	100°C	150°C
- Temperature Max (T_{Smax})	150°C	200°C
- Time (min to max) (t_s)	60~120 sec	60~180 sec
T_{Smax} to T_L		
- Ramp-up Rate	<3°C/sec	<3°C/sec
Time maintained above:		
- Temperature (T_L)	183°C	217°C
- Time (t_L)	60~150 sec	60~150 sec
Peak Temperature (T_P)	240°C +0/-5°C	260°C +0/-5°C
Time within 5°C of actual Peak Temperature (t_P)	10~30 sec	20~40 sec
Ramp-down Rate	<6°C/sec	<6°C/sec
Time 25°C to Peak Temperature	<6 minutes	<8 minutes

3. Flow (wave) soldering (solder dipping)

Products	Peak temperature	Dipping time
Pb devices.	245°C ±5°C	5sec ±1sec
Pb-Free devices.	260°C +0/-5°C	5sec ±1sec