

isc Silicon NPN Power Transistor

2SC1367

DESCRIPTION

- With TO-3 Package
- High voltage
- Wide area of safe operation
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Power amplifier applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	1000	V
V_{CEO}	Collector-Emitter Voltage	600	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	1.0	A
P_C	Collector Power Dissipation	50	W
T_J	Junction Temperature	-65~200	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-65~200	$^{\circ}\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	3.5	$^{\circ}\text{C/W}$



isc Silicon NPN Power Transistor**2SC1367****ELECTRICAL CHARACTERISTICS****T_c=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =0.5A; I _B = 0.1A			5.0	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C =0.5A; I _B = 0.1A			1.5	V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 10mA; I _B = 0	600			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 1mA; I _C = 0	5			V
h _{FE}	DC Current Gain	I _C =0.2A; V _{CE} = 10V	30		120	
I _{CBO}	Collector Cutoff Current	V _{CB} = 1000V ; I _E = 0			100	uA
I _{EBO}	Emitter Cutoff Current	V _{EB} =5V; I _C = 0			100	uA

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.