

# isc Silicon NPN Power Transistor

## 2SD1301

### DESCRIPTION



- High Breakdown Voltage-  
:  $V_{CBO} = 1500V$  (Min)
- High Switching Speed
- Low Collector Saturation Voltage-  
:  $V_{CE(sat)} = 3.0V$  (Max.) @  $I_C = 1A$
- Wide area of safe operation
- Built-in Damper Diode
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

### APPLICATIONS

- Designed for color TV horizontal output applications.

### ABSOLUTE MAXIMUM RATINGS( $T_a = 25^\circ C$ )

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	1500	V
$V_{CES}$	Collector- Emitter Voltage( $V_{BE} = 0$ )	1500	V
$V_{EBO}$	Emitter-Base Voltage	5	V
$I_C$	Collector Current- Continuous	2	A
$I_{CM}$	Collector Current-Peak	8	A
$P_C$	Collector Power Dissipation @ $T_C = 25^\circ C$	45	W
$T_J$	Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature Range	-65~150	$^\circ C$



**isc Silicon NPN Power Transistor****2SD1301****ELECTRICAL CHARACTERISTICS****T<sub>C</sub>=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V <sub>EB0</sub>	Emitter-Base Breakdown Voltage	I <sub>E</sub> = 500mA; I <sub>C</sub> = 0	5.0			V
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 1A; I <sub>B</sub> = 0.4A			3.0	V
V <sub>BE(sat)</sub>	Base-Emitter Saturation Voltage	I <sub>C</sub> = 1A; I <sub>B</sub> = 0.4A			1.5	V
I <sub>CBO</sub>	Collector Cutoff Current	V <sub>CB</sub> = 750V; I <sub>E</sub> = 0			50	μ A
		V <sub>CB</sub> = 1500V; I <sub>E</sub> = 0			1	mA
h <sub>FE</sub>	DC Current Gain	I <sub>C</sub> = 1A; V <sub>CE</sub> = 10V	3		12	
V <sub>ECF</sub>	C-E Diode Forward Voltage	I <sub>F</sub> = 4A			2.5	V
t <sub>s</sub>	Storage Time	I <sub>C</sub> = 1A, I <sub>Bend</sub> = 0.4A			6.0	μ s
t <sub>f</sub>	Fall Time				0.8	μ s

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.