


# IRFP264PbF

## HEXFET® Power MOSFET

- Dynamic dv/dt Rating
- Repetitive Avalanche Rated
- Isolated Central Mounting Hole
- Fast Switching
- Ease of Paralleling
- Simple Drive Requirements
- Lead-Free



$$V_{DSS} = 250V$$


$$R_{DS(on)} = 0.075\Omega$$

$$I_D = 38A$$

### Description

Third Generation HEXFETs from International Rectifier provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The TO-247 package is preferred for commercial-industrial applications where higher power levels preclude the use of TO-220 devices. The TO-247 is similar but superior to the earlier TO-218 package because of its isolated mounting hole. It also provides greater creepage distance between pins to meet the requirements of most safety specifications.



### Absolute Maximum Ratings

|                           | Parameter                                 | Max.                  | Units |
|---------------------------|-------------------------------------------|-----------------------|-------|
| $I_D @ T_C = 25^\circ C$  | Continuous Drain Current, $V_{GS} @ 10 V$ | 38                    | A     |
| $I_D @ T_C = 100^\circ C$ | Continuous Drain Current, $V_{GS} @ 10 V$ | 24                    |       |
| $I_{DM}$                  | Pulsed Drain Current ①                    | 150                   |       |
| $P_D @ T_C = 25^\circ C$  | Power Dissipation                         | 280                   | W     |
|                           | Linear Derating Factor                    | 2.2                   | W/°C  |
| $V_{GS}$                  | Gate-to-Source Voltage                    | $\pm 20$              | V     |
| $E_{AS}$                  | Single Pulse Avalanche Energy ②           | 1000                  | mJ    |
| $I_{AR}$                  | Avalanche Current ①                       | 38                    | A     |
| $E_{AR}$                  | Repetitive Avalanche Energy ①             | 28                    | mJ    |
| dv/dt                     | Peak Diode Recovery dv/dt ③               | 4.8                   | V/ns  |
| $T_J$                     | Operating Junction and                    | -55 to +150           | °C    |
| $T_{STG}$                 | Storage Temperature Range                 |                       |       |
|                           | Soldering Temperature, for 10 seconds     | 300 (1.6mm from case) |       |
|                           | Mounting Torque, 6-32 or M3 screw         | 10 lbf•in (1.1 N•m)   |       |

### Thermal Resistance

|                 | Parameter                           | Min. | Typ. | Max. | Units |
|-----------------|-------------------------------------|------|------|------|-------|
| $R_{\theta JC}$ | Junction-to-Case                    | —    | —    | 0.45 | °C/W  |
| $R_{\theta CS}$ | Case-to-Sink, Flat, Greased Surface | —    | 0.24 | —    |       |
| $R_{\theta JA}$ | Junction-to-Ambient                 | —    | —    | 40   |       |


# IRFP264PbF

International  
Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)





|                                 | Parameter                            | Min. | Typ. | Max.  | Units               | Test Conditions                                                     |
|---------------------------------|--------------------------------------|------|------|-------|---------------------|---------------------------------------------------------------------|
| $V_{(BR)DSS}$                   | Drain-to-Source Breakdown Voltage    | 250  | —    | —     | V                   | $V_{GS}=0V$ , $I_D=250\mu A$                                        |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | 0.37 | —     | V/ $^\circ\text{C}$ | Reference to $25^\circ\text{C}$ , $I_D=1mA$                         |
| $R_{DS(on)}$                    | Static Drain-to-Source On-Resistance | —    | —    | 0.075 | $\Omega$            | $V_{GS}=10V$ , $I_D=23A$ ④                                          |
| $V_{GS(th)}$                    | Gate Threshold Voltage               | 2.0  | —    | 4.0   | V                   | $V_{DS}=V_{GS}$ , $I_D=250\mu A$                                    |
| $g_{fs}$                        | Forward Transconductance             | 20   | —    | —     | S                   | $V_{DS}=50V$ , $I_D=23A$ ④                                          |
| $I_{DSS}$                       | Drain-to-Source Leakage Current      | —    | —    | 25    | $\mu A$             | $V_{DS}=250V$ , $V_{GS}=0V$                                         |
|                                 |                                      | —    | —    | 250   |                     | $V_{DS}=200V$ , $V_{GS}=0V$ , $T_J=125^\circ\text{C}$               |
| $I_{GSS}$                       | Gate-to-Source Forward Leakage       | —    | —    | 100   | nA                  | $V_{GS}=20V$                                                        |
|                                 | Gate-to-Source Reverse Leakage       | —    | —    | -100  |                     | $V_{GS}=-20V$                                                       |
| $Q_g$                           | Total Gate Charge                    | —    | —    | 210   | nC                  | $I_D=38A$                                                           |
| $Q_{gs}$                        | Gate-to-Source Charge                | —    | —    | 35    |                     | $V_{DS}=200V$                                                       |
| $Q_{gd}$                        | Gate-to-Drain ("Miller") Charge      | —    | —    | 98    |                     | $V_{GS}=10V$ See Fig. 6 and 13 ④                                    |
| $t_{d(on)}$                     | Turn-On Delay Time                   | —    | 22   | —     | ns                  | $V_{DD}=125V$                                                       |
| $t_r$                           | Rise Time                            | —    | 99   | —     |                     | $I_D=38A$                                                           |
| $t_{d(off)}$                    | Turn-Off Delay Time                  | —    | 110  | —     |                     | $R_G=4.3\Omega$                                                     |
| $t_f$                           | Fall Time                            | —    | 92   | —     |                     | $R_D=3.2\Omega$ See Figure 10 ④                                     |
| $L_D$                           | Internal Drain Inductance            | —    | 5.0  | —     | nH                  | Between lead, 6 mm (0.25in.) from package and center of die contact |
| $L_S$                           | Internal Source Inductance           | —    | 13   | —     |                     |                                                                     |
| $C_{iss}$                       | Input Capacitance                    | —    | 5400 | —     | pF                  | $V_{GS}=0V$                                                         |
| $C_{oss}$                       | Output Capacitance                   | —    | 870  | —     |                     | $V_{DS}=25V$                                                        |
| $C_{rss}$                       | Reverse Transfer Capacitance         | —    | 150  | —     |                     | $f=1.0MHz$ See Figure 5                                             |


## Source-Drain Ratings and Characteristics

|          | Parameter                              | Min.                                                                      | Typ. | Max. | Units   | Test Conditions                                                                                                                                      |
|----------|----------------------------------------|---------------------------------------------------------------------------|------|------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| $I_S$    | Continuous Source Current (Body Diode) | —                                                                         | —    | 38   | A       | MOSFET symbol showing the integral reverse p-n junction diode.  |
| $I_{SM}$ | Pulsed Source Current (Body Diode) ①   | —                                                                         | —    | 150  |         |                                                                                                                                                      |
| $V_{SD}$ | Diode Forward Voltage                  | —                                                                         | —    | 1.8  | V       | $T_J=25^\circ\text{C}$ , $I_S=38A$ , $V_{GS}=0V$ ④                                                                                                   |
| $t_{rr}$ | Reverse Recovery Time                  | —                                                                         | 410  | 620  | ns      | $T_J=25^\circ\text{C}$ , $I_F=38A$                                                                                                                   |
| $Q_{rr}$ | Reverse Recovery Charge                | —                                                                         | 5.7  | 8.6  | $\mu C$ | $di/dt=100A/\mu s$ ④                                                                                                                                 |
| $t_{on}$ | Forward Turn-On Time                   | Intrinsic turn-on time is negligible (turn-on is dominated by $L_S+L_D$ ) |      |      |         |                                                                                                                                                      |


### Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature (See Figure 11)
- ②  $V_{DD}=50V$ , starting  $T_J=25^\circ\text{C}$ ,  $L=1.1mH$ ,  $R_G=25\Omega$ ,  $I_{AS}=38A$  (See Figure 12)
- ③  $I_{SD}\leq 38A$ ,  $di/dt\leq 210A/\mu s$ ,  $V_{DD}\leq V_{(BR)DSS}$ ,  $T_J\leq 150^\circ\text{C}$
- ④ Pulse width  $\leq 300\mu s$ ; duty cycle  $\leq 2\%$ .







**Fig 5.** Typical Capacitance Vs. Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs. Gate-to-Source Voltage




**Fig 7.** Typical Source-Drain Diode Forward Voltage




**Fig 8.** Maximum Safe Operating Area




**Fig 9.** Maximum Drain Current Vs. Case Temperature



**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Case

# IRFP264PbF


International  
**IOR** Rectifier




**Fig 12a.** Unclamped Inductive Test Circuit




**Fig 12b.** Unclamped Inductive Waveforms



**Fig 13a.** Basic Gate Charge Waveform



**Fig 12c.** Maximum Avalanche Energy Vs. Drain Current



**Fig 13b.** Gate Charge Test Circuit


**Appendix A:** Figure 14, Peak Diode Recovery  $dv/dt$  Test Circuit – See page 1505

**Appendix B:** Package Outline Mechanical Drawing – See page 1511

International  
**IOR** Rectifier


## TO-247AC Package Outline

Dimensions are shown in millimeters (inches)



## TO-247AC Part Marking Information

**EXAMPLE:** THIS IS AN IRFPE30  
WITH ASSEMBLY  
LOT CODE 5657  
ASSEMBLED ON WW 35, 2000  
IN THE ASSEMBLY LINE "H"  
**Note:** "P" in assembly line  
position indicates "Lead-Free"



Data and specifications subject to change without notice.

International  
**IOR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903  
12/03



### Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.