


NPN Transistors

2SC4541

■ Features

- Low saturation voltage
- High speed switching time
- Small flat package
- $P_c = 1.0$ to 2.0 W (mounted on ceramic substrate)
- Complementary to 2SA1736

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	V_{CB0}	80	V
Collector - Emitter Voltage	V_{CE0}	50	
Emitter - Base Voltage	V_{EB0}	6	
Collector Current - Continuous	I_C	3	A
Base Current	I_B	0.6	
Collector Power Dissipation (Note.1)	P_c	500	mW
		1000	
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 to 150	

Note.1: Mounted on ceramic substrate ($250\text{ mm}^2 \times 0.8\text{ t}$)

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	V_{CB0}	$I_C = 100\text{ uA}, I_E = 0$	80			V
Collector- emitter breakdown voltage	V_{CE0}	$I_C = 10\text{ mA}, I_B = 0$	50			
Emitter - base breakdown voltage	V_{EB0}	$I_E = 100\text{ uA}, I_C = 0$	6			
Collector-base cut-off current	I_{CBO}	$V_{CB} = 80\text{ V}, I_E = 0$			0.1	uA
Emitter cut-off current	I_{EBO}	$V_{EB} = 6\text{ V}, I_C = 0$			0.1	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 1.5\text{ A}, I_B = 75\text{ mA}$			0.5	V
Base - emitter saturation voltage	$V_{BE(sat)}$	$I_C = 1.5\text{ A}, I_B = 75\text{ mA}$			1.2	
DC current gain	h_{FE}	$V_{CE} = 2\text{ V}, I_C = 100\text{ mA}$	120		400	us
		$V_{CE} = 2\text{ V}, I_C = 2\text{ A}$	40			
Turn-on time	t_{on}	See specified Test Circuit		0.1		
Storage time	t_{stg}			0.5		
Fall time	t_r			0.1		
Collector output capacitance	C_{ob}	$V_{CB} = 10\text{ V}, I_E = 0, f = 1\text{ MHz}$		20		pF
Transition frequency	f_T	$V_{CE} = 2\text{ V}, I_C = 100\text{ mA}$		100		MHz


■ Marking

Marking	K*D
---------	-----

NPN Transistors





2SC4541

Switching Time Test Circuit



$I_{B1} = -I_{B2} = 75 \text{ mA}$,
DUTY CYCLE $\leq 1\%$

■ Typical Characteristics



NPN Transistors

2SC4541

■ Typical Characteristics

